

HDFocus Catalogue Video Wall Display HDV49

www.hd-focus.com




HDV49

49" Video Wall Display

1. Product Outlook



Front



HDV49 Specification



2. Main Features

- ✓ Professional industrial grade 49" TFT- LCD screen, LED back light;
- Unique embedded in structure which is designed for video wall display, perfect display screen of every detail;
- ✓ All-in-one solution with built in video wall processor;
- ✓ Ultra narrow bezel of 3.5mm;
- \checkmark High brightness of 500 cd/m², with contrast of 4000: 1;
- Abundant input and output interface with VGA、 HDMI、 DVI、 BNC, RS232 connectors;
- ✓ High quality picture effect, support 3D digital comb filter (PAL / NTSC), 3D digital noise reduction, progressive scan, exclusive technology to make screen more black, WCG-CCFL bright backlight colors
- ✓ Industrial level design, support 24/7 working.

Display Screen	49" TFT-LCD panel with LED backlight
Display Ratio	16:9
Bezel	3.5mm
Color	16.77M colors
Display area	1073.8*604mm
Resolution	1920*1080
Brightness	500cd/m2
Contrast	4000:1
View Angle	178° left and right, up and down

3. Display

HDV49 Specification



4. Video Wall Processor Main Features

- ✓ All-in-one solution with built in video wall processor, support to full picture splicing display with splitter; and also can work together with matrix switcher and video wall processor;
- ✓ Multi channels parallel processing, signal processing powerful;
- ✓ RS232 serial remote control; each unit to support two-way RS232 loop out;
- \checkmark Does not need to dial the code to set up ID, the debugging is simple;
- ✓ Support to customize 4K processor, to achieve the total video wall display achieve 4K resolution.




Processor Built-in



5. Interface


USB	USB*1
HDMI Input	HDMI*1
VGA Input	VGA*1
DVI Input	DVI-I*1
AV Input (BNC)	AV Input*2
AV Output (BNC)	AV Output*2
RJ 45 Input	RJ45 Input*1
RJ 45 Output	RJ45 Output*2






6. Others

Format	PAL, NTSC
Voltage	DC12V/AC100-240V 50/60Hz
Power Output	≤ 200W
Working Temperature	0 - 60 °C
Product Dimension	1075.6×605.8×110.9mm







7. Software: Multi-Screen Display System

💻 HDFocus Video Wall System P200		– 🗆 ×
System Setting Language Help		
Admin Ket Soreen ON	Screen OFF Functiog Set Screen Addr	Remote Lan reflesh Rolling Text
1 HDMI	2 HDMI	COM set
3 HDMI	4 HDMI	Matrix Enable_Execute Matrix Type HDM_944
		🔽 Mix Matrix
		Open COM Close COM
		Auto Adjust User Reset
<u></u>		Power on Power off
	🏧 Border Effect [🛄 Matrix Config 🛛 🔁 Scene Preset 🛛 🔳 Combination Set 🗎	
O HDFocus	VGA: SANYANG_VGA VO OK VGA Matrix Use COM Onl	Open Matrix Output Set Open Delay: 50ms
Com Closed	2016-07-22 15:09:09 Oper	ator

Software Interface

Shenzhen HDFocus Technology Co., Ltd

Add: 5th Floor, 51 Building, Bantian No. 3 Industrial Park, Bantian Community, Bantian Street, Longgang, Shenzhen, China 518129 T: 0086 755 8520 4829

Web: www.hd-focus.com